

4130 Road Widener

LeeBoy



Performance Features:

The LeeBoy 4130 road widener is a versatile machine that meets your road widening needs. The narrow width design allows for shipping without a permit while shiftable conveyor and foldable hopper wings allow precise placement of material to either side of the machine. Operator console easily shifts from side-to-side and allows a clear view into the front hopper and of the material flow to the strike-off. A tilting front hopper improves trailer load angle to 14.5°. Extendable push rollers insure a variety of trucks can be used to feed the hopper.

- 74 hp (55 kw) Cummings Tier 4 Final Engine
- Width of Spread: up to 8' (2.44 m)
- Contoured Strike-Off
- 8' 6" Shipping Width - No Permit Required
- 24" (.609 m) Wide Heat-Resistant Conveyor Belt
- 2.2 Cubic Yards Hopper Capacity
- Tilting Hopper, 14.5° Load Angle
- Dual-Position Control Station
- Hydrostatic Drive and Traction Control System
- Extendable Push Rollers
- Unobstructed View from the Operator's Station



4130 Road Widener Specifications



Dimensions	<ul style="list-style-type: none"> - Length: 20' 6" (6.24 m) - Width: 8' 6" (2.9 m) shipping 9' 8" (2.94 m) working - Height: 8' 9" (2.67 m) - Wheelbase: 9' 9" (2.97 m) - Total Weight: 22,670 lbs (10,283 kg) 	Brakes	<ul style="list-style-type: none"> - Hydrostatic traction drive primary braking - Parking brake controlled by electric switch on operator's console - Failsafe parking brake - Foot pedal hydraulic service break
Engine	Cummins Tier 4 Final engine, 74 hp (55 kw)	Operator's Controls	<ul style="list-style-type: none"> - Dual control stations, each equipped with: Foot actuated conveyor function switch - Control functions on the operator's console: Main power, starter throttle, horn, conveyor speed, shuttle and discharge direction, strike off lift and lateral movement, hopper wing, steering, parking brakes
Capacities	<ul style="list-style-type: none"> - Fuel: 51 gallons (208 l) - Hydraulic reservoir: 61 gallons (230 l) 	Instrumentation	PV480 digital display for: <ul style="list-style-type: none"> - Engine oil pressure - Water temperature - Voltmeter and hydraulic oil temperature - Tachometer - Hour meter - Engine RPMs
Hopper	<ul style="list-style-type: none"> - 2.2 cubic yards capacity - Tilting hopper 14.5° load angle - Two bearing equipped push rollers, truck entry 9' 3" (2.81 m) 	Tires	<ul style="list-style-type: none"> - Two 385/65R 22.5 radial - Two 425/65R 22.5 radial
Conveyor System	<ul style="list-style-type: none"> - 24" (.609 m) wide, high temperature service nitrile belt travelling on tapered roller bearing support rollers - Independent, variable speed, hydrostatic, dual end drive system - Conveyor speed: 0 to 448' per minute (5.09mph) - Equipped with adjustable wipers to prevent material buildup - Shiftable up to 18" (.45 m) side-to-side 	Optional Equipment	<ul style="list-style-type: none"> - Dual strike-off group - 1' (.3 m) contoured strike-off section - 3' (.9 m) contoured strike-off section - 2-3' (.6-.9 m) telescoping contoured strike-off section, only one mounted per side - TopCon P-32 system controls – single grade and slope, sonic - Washdown system with 2 hose reels and 7 gal lon (26 l) tank - Umbrella - Truck Hitch
Material Spread Strike Off	<ul style="list-style-type: none"> - Contoured strike off for controlled spread of material width, depth and slope - Width of spread: up to 8' (2.44 m) - Basic strike off consist of one 1' (.304 m) and one 2' - 3' (.6 - .91 m) section, extendable - Raised, lowered, extended and retracted hydraulically with manual stops for fine adjustment of elevation and slope - Outer edger plate assemble included - 12" (304 m) above and below grade - On board storage for strike offs and strike off supports 		



VT LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
 For additional products or information, visit our website: www.LeeBoy.com

BR-6501.0-EN This document contains information applicable for the U.S. and U.S. Territories. For International product availability, specifications and support, please contact your authorized LeeBoy representative. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy Group reserves the right to modify at any time.

