

# 250 Tack Tank

# LeeBoy



Perfect for the all-inclusive commercial paving contractor, the 250 Tack Distributor provides a perfectly sized tank for small to large projects including parking lots, patching, driveways or soil stabilization. Daily task can be completed with ease by relying on the trouble-free Honda powered engine and the proven reliable user-friendly design. Uniquely configurable, the customizable options give the contractor the ability to create a solution specific to their exact needs.

## Performance Features:

- 250 Gallon (946 l) Capacity Tank
- 4.8 hp (3.6 kw) Honda Engine
- 6' (1.8 m) Wand with On/Off Valve
- 40' (12.19 m) Heavy-Duty Recoil Hose Reel
- 4,500 lbs (2,041 kg) Loaded Weight
- Rear Tank Sampling Valve
- Two 54,000 BTU Propane Burners
- Trailer or Skid-Mount Configurations
- Electric brakes
- Emergency Brake-Away System
- Optional Accessories Available



# 250 Tack Distributor Specifications



Tank Size	250 gallons (946 l)
Dimensions (Trailer Configuration)	<ul style="list-style-type: none"> <li>- Length: 11' 6" (3.51 m)</li> <li>- Width: 6' 6" (1.98 m)</li> <li>- Height: 7' 6" (2.29 m)</li> <li>- Shipping Weight: 2,179 lbs (988.3 kg)</li> </ul>
Dimensions (Skid Mount Configuration)	<ul style="list-style-type: none"> <li>- Length: 6' 6" (1.98 m)</li> <li>- Width: 4' 4" (1.32 m)</li> <li>- Height: 5' 11" (1.8 m)</li> <li>- Shipping Weight: 1,380 lbs (626 kg)</li> </ul>
Engine	Honda – 4.8 hp (3.6 kw)
Capacities	- Fuel: 1 gallon (3.79 l)
Tank Dimensions	<ul style="list-style-type: none"> <li>- Length: 48.5" (1.23 m)</li> <li>- Width: 48.5" (1.23 m)</li> <li>- Height: 32.5" (.825 m)</li> </ul>
Asphalt Pump	- Specially designed 7 gallons per minute (26.5 lmp) pump
Heat System	<ul style="list-style-type: none"> <li>- Two 54,000 BTU propane burners</li> <li>- One start burner</li> <li>- 30 lbs (13.6 kg) propane fuel tank</li> </ul>
Temperature Gauge	- 50 - 300° F (10 - 149° C)
Flush Tank	- 7 gallons (26.5 l) tank with suck back valve

Hose and Reel	- .5" x 40' (13 mm x 12.19 m) heavy-duty recoil hose reel
Wand	<ul style="list-style-type: none"> <li>- 6' (1.829 m) wand with cold handles</li> <li>- On/off valve</li> <li>- Removable spray tip</li> </ul>
Fill Spout	10" x 10" (254 x 254 mm) with splash plate
Clean Out	- 4" (102 mm)
Access Valve	- 1" (25 mm)
Optional Equipment	<ul style="list-style-type: none"> <li>- Electric start (available on Honda-Gas and Hatz-Diesel engine)</li> <li>- 5 hp Hatz diesel engine (pull start)</li> <li>- Insulated tank</li> <li>- Auto ignition burners (only available with electric start engine)</li> <li>- Auto ignition burners with outfire protection (only available with electric start engines)</li> <li>- 8' (2.4 m) spray bar</li> <li>- Spray bar lift (only available on skid-mounted unit)</li> <li>- In-truck controls (requires 8' spray bar option)</li> <li>- Overnight heater</li> <li>- Surge brakes (only available on trailer mounted unit)</li> <li>- Pintle eye</li> </ul>



VT LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300  
 For additional products or information, visit our website: [www.LeeBoy.com](http://www.LeeBoy.com)



BR-4002.1-EN This document contains information applicable for the U.S. and U.S. Territories. For International product availability, specifications and support, please contact your authorized LeeBoy representative. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy Group reserves the right to modify at any time.