

500 Tack Tank

LeeBoy



Contractors who want to embrace both small and large-scale projects demand the practicality of the 500 Tack Tank. Proven reliable and easy-to-use, operators are given trouble-free Honda power and safety-designed electric brakes at both axles with emergency brakes away reassurance. Trailer or skid-mounted configurations allow commercial pavers with an efficient yet adequate method for tack coating on job sites. To make this offering even more spectacular, it can be customized using numerous options to fit your exact needs.

Performance Features:

- 500 Gallon (1,892 l) Capacity Tank
- 4.8 hp (3.6 kw) Honda Engine
- 6' (1.8 m) Wand with On/Off Valve
- 40' (12.19 m) Heavy-Duty Recoil Hose Reel
- 7,270 lbs (3,298 kg) Loaded Weight
- Rear Tank Sampling Valve
- Two 54,000 BTU Propane Burners
- Trailer or Skid-Mount Configurations
- Electric brakes
- Emergency Brake-Away System
- Optional Accessories Available



500 Tack Distributor Specifications



Tank Size	500 gallons (1,892 l)
Dimensions (Trailer Configuration)	<ul style="list-style-type: none"> - Length: 14' 6" (4.42 m) - Width: 6' 6" (1.98 m) - Height: 6' 4" (1.93 m) - Shipping Weight: 3,050 lbs (1,370 kg)
Dimensions (Skid Mount Configuration)	<ul style="list-style-type: none"> - Length: 9' 9" (2.97 m) - Width: 4' 6" (1.37 m) - Height: 5' 6" (1.68 m) - Shipping Weight: 2,300 lbs (1,043 kg)
Engine	Honda – 4.8 hp (3.6 kw)
Capacities	- Fuel: 1 gallon (3.79 l)
Tank Dimensions	<ul style="list-style-type: none"> - Length: 7' (2.13 m) - Width: 48.5" (1.23 m) - Height: 32.5" (.825 m)
Asphalt Pump	- Specially designed 7 gallons per minute (26.5 lpm) pump
Heat System	<ul style="list-style-type: none"> - Two 54,000 BTU propane burners - One starter burner - 30 lbs (13.6 kg) propane fuel tank
Temperature Gauge	- 50 - 300° F (10 - 149° C)
Flush Tank	- 7 gallons (26.5 l) tank with suck back valve

Hose and Reel	- .5" x 40' (13 mm x 12.19 m) heavy-duty recoil hose reel
Wand	<ul style="list-style-type: none"> - 6' (1.829 m) wand with cold handles - On/off valve - Removable spray tip
Fill Spout	10" x 10" (254 x 254 mm) with splash plate
Clean Out	- 4" (102 mm)
Access Valve	- 1" (25 mm)
Optional Equipment	<ul style="list-style-type: none"> - Electric start (available on Honda-Gas and Hatz-Diesel engine) - 5 hp Hatz diesel engine (pull start) - Insulated tank - Auto ignition burners (only available with electric start engine) - Auto ignition burners with outfire protection (only available with electric start engines) - 8' (2.4 m) spray bar - Spray bar lift (only available on skid-mounted unit) - In-truck controls (requires 8' spray bar option) - Overnight heater - Surge brakes (only available on trailer mounted unit)



VT LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
 For additional products or information, visit our website: www.LeeBoy.com



BR-4003.1-EN This document contains information applicable for the U.S. and U.S. Territories. For International product availability, specifications and support, please contact your authorized LeeBoy representative. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy Group reserves the right to modify at any time.